

TYPICAL PERFORMANCE DATA
XE PREMIUM ENERGY EFFICIENT : TEFC, TEFC-XEX, TEFC-XP
 3 Phase - Continuous Duty - Normal Torque - Design B
 1.15 S.F. - Class F Insulation

H.P.	RPM	FRAME SIZE	AMPERES @ 480V										EFFICIENCY					NEMA EFF.					POWER FACTOR					RPM					TORQUE LB.F.T.					PF CORR	BOUND PRESS @ 3 FT TYPICAL	PERFORMANCE DATA DESIGN NUMBER					
			LOAD					LOCKED					LOAD					NEMA					LOAD					FL					BO								PU				
			4/4	3/4	2/4	1/4	AMP/3 CODE	PU	BD	4/4	3/4	2/4	1/4	NOM	MIN	4/4	3/4	2/4	1/4	FL	BO	PU	FL	BO	PU	LR	FL	BO	PU	LR															
1.5	900	L182T	1.7	1.5	1.3	1.2	0.1	J	9.1	5.8	83.5	83.0	79.9	70.3	82.5	81.5	84.4	55.8	43.7	27.3	870	700	-	6.04	17.7	9.80	9.80	0.38	0.7	52	E1002A-B-002														

TYPICAL PERFORMANCE DATA
XE PREMIUM ENERGY EFFICIENT : TEFC, TEFC-XEX, TEFC-XP
 3 Phase - Continuous Duty - Normal Torque - Design B
 1.15 S.F. - Class F Insulation

H.P.	RPM	FRAME SIZE	AMPERES @ 480V										EFFICIENCY					NEMA EFF.					POWER FACTOR					RPM					TORQUE LB.F.T.					PF CORR	BOUND PRESS @ 3 FT TYPICAL	PERFORMANCE DATA DESIGN NUMBER					
			LOAD					LOCKED					LOAD					NEMA					LOAD					FL					BO								PU				
			4/4	3/4	2/4	1/4	AMP/3 CODE	PU	BD	4/4	3/4	2/4	1/4	NOM	MIN	4/4	3/4	2/4	1/4	FL	BO	PU	FL	BO	PU	LR	FL	BO	PU	LR															
30	300	300T8	56.6	42.8	30.4	20.5	302	G	330	211	94.3	94.7	94.6	92.3	94.1	93.0	97.7	88.5	81.3	81.8	85.7	3382	1440	73.8	195	115	135	4.0	8.0	72	E00975-A-A002														